

**Mechanical characteristics**

cable group  
  
interface dimensions acc. to assembly code  
panel piercing  
mating life

**Components**

centre contact  
outer contact  
tooth washer  
other metal parts  
insulator  
gasket  
o-ring

**Electrical characteristics**

impedance  
frequency  
voltage proof  
insulation resistance  
contact resistance  
    centre contact  
    outer contact

**Environmental**

operating temp.  
RoHS compliant

**Mechanische Eigenschaften**

Kabelgruppe  
  
Steckgesicht nach Montageanleitung  
Montagebohrung  
Steckzyklen

**Bauteile**

Innenkontakt  
Außenkontakt  
Fächerscheibe  
sonstige Metallteile  
Isolierung  
Dichtung  
O-Ring

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
    Innenkontakt  
    Außenkontakt

**Umgebung**

Betriebstemperatur  
RoHS konform

G 7: KX 22A, KX 3B, MRC 100 Flex (0.48L/1.5AF) Draka,  
RG-174/U, RG-188A/U, RG-316/U  
LMR-100A TMS  
IEC 61169-8  
A04  
Z004  
≥500


**Materials / Material**

CuBe2  
CuZn39Pb3  
CuSn6  
CuZn39Pb3  
PTFE  
silicone / Silikon  
NBR

**Finish / Oberfläche**

NiP-Au  
Cu2Ni5  
Cu2Ni5  
Cu2Ni5

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	05.01.2017	MA	
			gepr./ appr.	24.01.2017	BJ	ca./approx. 21,2
			Maßstab/ scale	Benennung/ title		
			2:1 (1:1)	BNC Bulkhead Jack BNC-Kabeleinbaubuchse		
			unt. Maß/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
			K	J01001A1318		
			Ersatz für/ replaces			
				<b>Telegärtner</b>		
				Maße/ dimensions: mm		
				Original : DIN A4		
				Blatt/ sheet 1 von/ of 1		