

Außenleiter / outer conductor
 Innenleiter / inner conductor
 Crimprohr / crimp ferrule
 sonstige Metallteile / other metal parts
 Isolierung / insulator
 Dichtung / gasket

CuZn39Pb3
 CuPb1.15Ni1 (C97)
 CuZn38Pb1.5
 CuZn39Pb3
 PTFE
 Silikon



Cu2Ni5
 Cu1Ni2Au0.8
 Cu2Ni5
 Cu2Ni5

Kabel / cable

G 7: RG-174/U; RG-188A/U; RG-316/U;
 KX 22A; KX 3B

Montage / assembly

A3416 (b)

b a	16172 15482	16.12.04 19.04.04	BJ MA	2004	Datum/date	Name/name	Werkstoff/ material
				gez./drawn	15.03.	MA	
				gepr./appr.	19.03.04	BJ	Oberfläche/ finish
				Norm./stand.			
Maßstab/scale		Benennung/title					
2:1		R-TNC-Kabelstecker (a) R-TNC Straight Plug					
untol. Maße/ dim. without tolerances according to		Untert./doc.type	Zeichnungsnr./drawing no.		 Maße/dimensions: mm Original: DIN A4		
		K	J01010R0001				
Änd./rev. Index		Änderungsmittellung/ revision code		Datum/ date		Name/ name	
				Ersatz für/ replaces			